

CICO SEALOCOAT

Clear Acrylic Resin Based Water Repellent Coating

Clear, acrylic resin based water repellent coating for exterior exposed surfaces.

USES

Water repellent. Suitable for concrete block, concrete, brick, stone, cement plaster. Prevents moisture damage to interior surfaces such as plaster cracking and paint blistering. Will also restore colour and reseal all panels.

FEATURES

- Quick action-block work becomes highly water repellent in 2 or 3 hours.
- Long lasting-tests show years of dependable protection.
- Seals surface-moisture completely excluded. Protective seal prevents stain and dirt penetration.
- Reduces weather staining-vertical surfaces tend to be self cleaning.
- Invisible-causes no change in appearance of the surface coated.
- Film will not yellow or darken on aging.
- Low temperature application-may be applied at temperature down to freezing.

RECOMMENDED SYSTEM

After thorough surface preparation, a two coat treatment with an interval of 2 to 3 hours between coats is recommended.

APPLICATION DATA

Surface Preparation

Inspect areas to be treated for cracks and loose mortar. Caulk or repair cracks or loose joints. Surface should be dry, clean and cured for 28 days. Any wax, oil or grease should be removed by swabbing with a suitable solvent, followed by a thorough scrubbing with a mild detergent. If heavy rain has occurred, drying for 2 or 3 days is desirable, depending on ambient temperatures.

Application

CICO SEALOCOAT is preferably applied by low pressure spray equipment (3–10Kg/cm²). Apply 2 (two) coats, working from top to bottom of the area with an interval of 2 to 3 hours between coats. **CICO SEALOCOAT** may also be applied by brush method use a wide fine hair brush. Apply liberally.

CLEANING

Use Xylene

PROPERTIES

Temperature	Must not be applied at temperature below freezing (0°)
Flash point	Approx.40°C.
Specific Gravity	0.95
Thinning	Not recommended
Coverage/Dose Rate	4 - 5 m ² /litre in two coats depending on porosity and type of surface.
Drying Time	Allow 2 to 3 hours between coats.

STORAGE

If stored in dry in unopened containers, a shelf life of approximately 12 months could be expected.

SHELF LIFE

18 months.

PACKAGING

Available in 5 and 20 Ltr drum packing

Important Note:

All CICO products are sold in the market after strict Quality Control in line of ISO 9001 and guaranteed against any manufacturing defect. Although the basic formulation of Company's products generally remains unchanged, production refinements arising from continuing research and evaluation program may occasionally result in marginal changes in properties. CICO aspires to ensure that any recommendation, advice, test data, specification, method statement and other information given in this product datasheet is accurate and best of company's knowledge. Since, the company (CICO TECHNOLOGIES LTD) has no control over the selection of its product, applicators, application methodology, how and where it is applied, therefore, the company cannot accept any liability directly or indirectly arising from the use of its product. It is important to any customer, user or specifier satisfies him / herself that the product is suitable for the intended purpose including health, safety and environmental aspect. Unless or otherwise agreed in writing, all products of the company are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. All customers, users, specifiers should ensure that they examine the suitability of the product with company's latest product data sheet.

CICO TECHNOLOGIES LIMITED

Corp. Office: C-44/2, 1st & 2nd Floor, Okhla Industrial Area,
Phase -II, New Delhi-110 020
Tel. No: 91-11-4050 9400, Fax: 91-11-4050 9413
E-Mail: cicotech@cicogroup.com
Web Site: www.cicogroup.com



ISO 9001:2008
FM 54275

CTL/07-14/01