



CICO NO.2

Rapid/Quick Setting/Hardening Compounds for Cement

CICO NO.2 is an extra fast setting waterproofing/plugging compound. It is a red coloured liquid.

USES

CICO NO.2 is an excellent time tested liquid admixture for emergency / immediate repair work. Due to very fast setting property, **CICO NO.2** is used for instant leak plugging and quick fixing of nozzle and also widely used as plugging compound for basements, pipe joints, retaining walls, tunnels and sewage works, where water is pouring under pressure.

FEATURES

- Excellent quality plugging compound – consistent performance
- High early strength – plugging is completed within 5 minutes
- Simple application – excellent adhesion

APPLICATION

Cut back the opening of leaking hole to form concave shape tapering to a narrow mouth at the entrance, place the gelled cement/**CICO No.2** mass into the hold and keep the pressure on for 4 to 5 minutes.

DOSAGE

30 – 40% by weight of cement. It cannot be diluted with water

SHELF LIFE

18 months if unopened.

PACKING

Available in 1 kg, 5 Kg, 20 Kg, 50 Kg and 225 Kg

STORAGE

Keep in a cool place and protect from extremes of heat.

HEALTH & SAFETY

Highly alkaline. Use gloves. Non-toxic, non-flammable.

TECHNICAL DATA

Colour	Red liquid
Specific Gravity	1.25 ± 0.02
Chloride content	Nil
Setting Time	30 to 60 seconds
Cement compatibility	OPC not compatible with other admixtures

Important Note:

All CICO products are sold in the market after strict Quality Control in line of ISO 9001 and guaranteed against any manufacturing defect. Although the basic formulation of Company's products generally remains unchanged, production refinements arising from continuing research and evaluation program may occasionally result in marginal changes in properties. CICO aspires to ensure that any recommendation, advice, test data, specification, method statement and other information given in this product datasheet is accurate and best of company's knowledge. Since, the company (CICO TECHNOLOGIES LTD) has no control over the selection of its product, applicators, application methodology, how and where it is applied, therefore, the company cannot accept any liability directly or indirectly arising from the use of its product. It is important to any customer, user or specifier satisfies him / herself that the product is suitable for the intended purpose including health, safety and environmental aspect. Unless or otherwise agreed in writing, all products of the company are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. All customers, users, specifiers should ensure that they examine the suitability of the product with company's latest product data sheet.

CICO TECHNOLOGIES LIMITED

Corp. Office: C-44/2, 1st & 2nd Floor, Okhla Industrial Area,
Phase –II, New Delhi-110 020
Tel. No: 91-11-4050 9400, Fax: 91-11-4050 9413
E-Mail: cicotech@cicogroup.com
Web Site: www.cicogroup.com



ISO 9001:2008
FM 54275

CTL/07-14/01