

Sikafab 1

Glass Fiber Fabric for Coating Reinforcement

Description	Sikafab 1 is aspecially made glass fiber fabric for use with Sika FlexiSil and SikaTop Seal 109h. This is awoven fabric to impart high mechanical properties on both directions.
Uses	Sikafab 1 is used as a reinforcement for Sika FlexiSil and Sika Top Seal 109h. It is used on : Roof Basement Parapet Sunshed
Advantage	Sikafab 1 has the following advantages : <ul style="list-style-type: none"><input type="checkbox"/> High tensile strength<input type="checkbox"/> Flexible<input type="checkbox"/> Chemical resistant<input type="checkbox"/> Mildew proof
Size	Sikafab 1 is available in approximately 1 meter width and 100meter length
Instruction For use	Sikafab 1 has to be applied on green/ freshly applied Sika FlexiSil and Sika Top Seal 109h. Before application the fabric should be cut as per the length of the substrate. The cut pieces should be rolled again. Now after the liquid membrane has been applied, the fabric should be spread from one end and embedded by special Sika Roller. Wear spike shoe for this job. In the same process other pieces of fabric should be applied adjacent to the previous one. Make an overlap of 20mm along the entire length. After the first coat of membrane and fabric application is complete allow the membrane to harden. Then apply the second coat of the Sika membrane.



Sika India Pvt. Ltd.
Commercial
Complex II
620, D.H. Road
Kolkata – 700034
Tel. (033) 2447 2448/2449/2501/2505/9503
Fax (033) 2468 8688/2665
www.sikaindia.com